

2016 RENEGADE® ENDURO™ NEW

PACKAGE HIGHLIGHTS

- RAS™ 2 front suspension
- **REV-XS™ platform [NEW for 1200 4-TEC]**
- **NEW rMotion™ with Air RIDE rear suspension**
- **NEW 15 x 137 x 1.25-inch Ice Ripper XT track**
- HPG™ Plus aluminum front shocks
- **NEW Adjustable Pilot™ TS skis**
- Brembo brake with braided stainless-steel brake line
- RER™ electronic reverse
- Multifunction digital gauge with display
- 12 V power outlet and heated visor outlets for driver
- RF D.E.S.S.™ key
- REV-XP™ X® seat with 5 L / 1.3 gal of storage
- Backlit multifunction steering controls
- **NEW XC front bumper**

EXTRA HIGHLIGHTS

- 900 ACE™ & 1200 4-TEC®
- **Reversible throttle lever (thumb or finger activated) [NEW for 1200 4-TEC]**
- **iTC™ engine mapping modes (Standard, Sport or ECO™) [NEW for 1200 4-TEC]**
- **Learning Key™ included [NEW for 1200 4-TEC]**
- Engine oil cooler
- Mechanical reverse
- Extended heat exchanger for better cooling capacity [1200 4-TEC]



600 H.O. E-TEC shown

NEW features for 2016

ROTAX® ENGINE

	600 H.O. E-TEC®	800R E-TEC	900 ACE	1200 4-TEC
Engine details	Liquid-cooled, 3-D R.A.V.E.™		Liquid-cooled, four-stroke D.O.H.C., dry sump	
Cylinders	2		3	
Displacement	594.4cc / 36.3 in. ³	799.5cc / 48.8 in. ³	899cc / 54.9 in. ³	1170.7cc / 71.4 in. ³
Bore	72 mm / 2.8 in.	82 mm / 3.2 in.	74 mm / 2.9 in.	91 mm / 3.6 in.
Stroke	73 mm / 2.9 in.	75.7 mm / 3 in.	69.7 mm / 2.7 in.	60 mm / 2.4 in.
Maximum engine speed	8100 RPM	7900 RPM	7250 RPM	7800 RPM
Carburation	Electronic Direct Injection		EFI	
Recommended fuel type	Premium unleaded		Regular unleaded	
Minimum octane	91		87	
Fuel tank	40 liters / 10.6 gallons			
Oil tank capacity	3.7 liters / 3.9 quarts		3.3 liters / 3.5 quarts	3.5 liters / 3.7 quarts

COLOR

Northern Lichen

DIMENSIONS

Vehicle overall length	3110 mm / 122.4 in.
Vehicle overall width	1217 mm / 47.9 in.
Vehicle overall height	1210 mm / 47.6 in.
Ski stance	1077 mm / 42.4 in.
Ski overall length	1066 mm / 42 in.
Track nominal width	381 mm / 15 in.
Track nominal length	3487 mm / 137 in.
Track profile height	31.8 mm / 1.25 in. Ice Ripper XT

POWERTRAIN

Drive clutch type	TRA™ III	TRA VII	eDrive™ 2	
Driven clutch type	QRS		QRS (short shaft)	QRS
Engagement	3400 RPM	3800 RPM	2200 RPM	
Small sprocket number of teeth	25		24	
Large sprocket number of teeth	45		49	45
Drive sprocket number of teeth	8			
Drive sprocket diameter	183 mm / 7.2 in.			
Brake system	Brembo brake with braided stainless-steel brake line			

DRY WEIGHT

223 kg / 492 lb 227 kg / 501 lb 235 kg / 518 lb 246 kg / 543 lb

FEATURES

Frame	REV-XS [NEW for 1200 4-TEC]	Reverse	RER (600 H.O., 800R)	Mirrors	Optional
Skis	Pilot TS		Mechanical (900 ACE, 1200 4-TEC)	Windshield	375 mm / 15 in.
Seating	REV-XP X with storage			Runner	Adjustable blade 1/4
Handlebar	Aluminum with J-hooks	Heated throttle lever	Standard	Carbide configuration	102 mm / 4 in. at 90°
Riser block height	115 mm / 4.5 in.	Heated grips	Standard	Hitch	Optional
Electric start	Standard	Gauge	Multifunction		



CROSSOVER

RENEGADE ENDURO



1200 4-TEC shown



1200 4-TEC shown. Now with ITC and built on the REV-XS platform.

FEATURE HIGHLIGHTS



RAS 2 front suspension

A taller ski spindle, refined geometry and lighter components sharpen the sled's already precise handling, especially in extreme conditions.



NEW Air RIDE rear suspension

Tailors the ride for load or trail conditions via a rear air spring and an onboard compressor. Five preload settings are selectable on-the-fly via a handlebar rocker switch.



LinQ™ cargo system (option)

Our cargo attachment system is the hassle-free way to connect cargo bags or a fuel caddy to your sled in seconds.



NEW Adjustable Pilot TS skis

Radical new concept enables the rider to literally dial in the amount of ski bite for conditions and riding style in seconds. A knob adjacent to the ski leg raises or lowers the ski runner – fully extended for a very aggressive bite. There are 20 settings over a .5 in. / 12.5 mm range.



Multifunction gauge with LCD screen

GAUGE FEATURES

Speedometer	Standard
Tachometer	Standard
Fuel	Standard
Engine temperature	Standard

ski-doo

